

Detect dangerous gas leaks quickly and reliably

Portable Gas Leak Detector

Model SP-230 TYPE H2

CE Marking-compliant/ UKCA Marking-compliant product



- **Easy to recognize by LED**

Newly equipped with LED, it informs the user of alarm points, gas concentration, and operating status by color and scale.

- **Enhanced functions allow for work in dark places**

LED light illuminating the front.
The backlit buttons for easy operation.

- **One-push access to multiple functions**

Frequently used operations such as LED light ON/OFF, alarm/operation sound ON/OFF, and alarm point switching can be operated with single push.

- **Reliable assign for use even in harsh environments**

- Pass 2m drop testing
- Protection rating equivalent to IP67
- Usable across a wide range of temperature (-20°C to +55°C)

Model	SP-230
Type	TYPE H2
Detection principle	Hot-wire semiconductor type
Detection target gas	Hydrogen Gas (Refer to Detection target gas list)
Calibration gas	H ₂ /CH ₄
Concentration display	LCD bar meter + scale + LED
Detection range	Depends on target gas (Refer to Detection target gas list) (H ₂ /CH ₄ : 10~2000ppm)
Detection method	Pump suction type
Alarm setpoints	Default setting: 30ppm(H ₂ /CH ₄ : 10, 30, 150, 500, 2000ppm)
Display items	Operating status icon, flow confirmation icon, operation tone icon, alarm sound icons, alarm setpoint display, battery level icon, bar meter display, mode display, gas name/message display
Response time (for identical conditions)	Within 3 seconds
Gas alarm type	One-step alarm
Gas alarm indication	Lamp flashing, buzzer sounding
Gas alarm pattern	Auto reset
Fault alarm	Sensor abnormality/Low flow rate/Low battery voltage/System abnormality/Adjustment abnormality/Clock abnormality/Pump abnormality
Fault alarm icon	Lamp flashing/buzzer sounding/fault information display
Fault alarm pattern	Self-latching
Power source	AA alkaline batteries × 2
Continuous operating time	Approx. 13 hours (with alkaline dry batteries, at 25 °C, no alarm, no lighting)
Operating temperature/humidity range	-20 °C to +55 °C (no sudden fluctuations)/Up to 95 %RH (no condensation)
Protection level	IP67 equivalent
Certifications	CE marking, UKCA marking
External dimensions/weight	Approx. 41 mm (W) × 186 mm (H) × 38 mm (D) (excluding projections)/ Approx. 220 g (excluding dry batteries)

● Detection target gas list

Gas name (standard name)	Display	Scale 1 (ppm)	Scale 2 (ppm)	Scale 3 (ppm)	Scale 4 (ppm)	Scale 5 (ppm)
Methane (calibration gas)	CH ₄	10	30	150	500	2000
Hydrogen (calibration gas)	H ₂	10	30	150	500	2000
Acetylene	C ₂ H ₂	10	30	150	500	2000
Ethylene	C ₂ H ₄	10	30	150	500	2000
Ethane	C ₂ H ₆	10	30	150	500	2000
Propylene	C ₃ H ₆	10	30	150	500	2000
Propane	C ₃ H ₈	10	30	150	500	2000
Butadiene	C ₄ H ₆	10	30	150	500	2000
Isobutylene	C ₄ H ₈	10	30	150	500	2000
Normal butane	N-C ₄ H ₁₀	10	30	150	500	2000
Isobutane	I-C ₄ H ₁₀	10	30	150	500	2000
Cyclopentane	C ₅ H ₁₀	10	30	150	500	2000
N-hexane	N-C ₆ H ₁₄	10	30	150	500	2000
Freon 22	R22	10	50	200	1000	3000
Freon 134a	R134A	20	100	500	2000	5000
HFO-1234yf	R1234YF	10	50	200	500	1000

※This product is used for detecting ultra-low gas leaks, so the gas concentration values are approximations.

Even easier to see!

In addition to the conventional LCD display screen, an LED display is mounted. The current gas alarm point, gas concentration, and operating status are notified in color and on a scale.




Normal



Gas alarm

Work in dark places is also safe!

Enhanced functions ensure safety even when working in dark places, LED light illuminating the front, the backlit buttons for easy operation.



LED light



Button backlit

One-push access to multiple functions



LED light ON/OFF



Operation sound, alarm ON/OFF



Gas alarm point switching



Shortcut key assignments

Standard accessories

Numbers in parentheses are part NO.

Protective cover
(4126 9248 30)



Tapered nozzle
(4126 9249 10)



Hand strap
(0888 0605 90)



AA Alkaline batteries
(2753 3007 80) ※One battery



Replacement waterproof filters
5 pcs
(4126 9189 30)



Optional accessories

Numbers in parentheses are part NO.

Tertiary filters
5 pcs
(4126 9199 20)



Inspection gas
(0800 0904 10)



Humidifier tube
(4126 9227 80)



RIKEN KEIKI Co.,Ltd.

2-7-6 Azusawa, Itabashi-ku, Tokyo 174-8744, Japan
Phone : +81-3-3966-1113
Telefax : +81-3-3558-9110
E-mail : intdept@rikenkeiki.co.jp
Web : <https://www.rikenkeiki.co.jp/english>

※ The contents described in this catalog are subject to change without notice according to the performance improvement.

★ Distributed by:

UNISERVICE

UNISAFE

Uniservice Unisafe SRL

Via al S.N.S. della Guardia 58a - Genoa 16162 Italy

Phone (+39) 010-714-647

E-mail info@uniservicesafety.com

Web site www.uniservicesafety.com