



RIKEN KEIKI KOREA FIXED GAS DETECTION SYSTEM


- Reliable
- Customizing
- Cost -effective



RIKEN KEIKI KOREA

World leader in gas detection & sensor technology

C.O.T /LPG/PRODUCT CONTAINER SYSTEM




Specification

Sampling point	1-58 sampling points per System, plus 50 points sensor
Sampling time	(1) Complete cycle to be detected less than 30min. with MSC.1/Circ.1370 Annex 2-2.1
Measurement	Flammable gas (%LEL / %VOL) Oxygen H2S NH3 CO2
User interface	Switchboard / Touch screen (10") for choosing the sample point, alarm stop & reset, skip, etc.
Alarm settings	Fully adjustable between zero and full scale
Audible alarm	-95dB @ 30cm
Relay output	Gas alarm Sensor trouble, Flow fail, Communication fail, Controller trouble, Panel inside and other system abnormal alarms
Communication configuration	RS-485/RS-422 & MODBUS communication

Painting	Powder coating with customer's requirement
Ingress Protection	IP65
Fixing details	Self standing type / Wall mounting type
Filter equipment	On line filter Gas inlet port with filter Air filter MC filter etc
Power supply	AC220V, 60Hz / DC24V(optional)
Power consumption	Max. 500VA (Alarm condition)
Other function	Auto drain, counter pressure, Auto/Manual purge, etc Option : Printer module Repeater alarm unit with display
Approval	MED, ABS, DNV, KR, RINA type approved LR, BV, NK, CCS are available
Sales refer.	More than 760 vessels

LNG CARRIER SYSTEM



Specification

Sampling point	1-58 sampling points per System, plus 50 points sensor
Sampling time	(1) Complete cycle to be detected less than 30min. with MSC.1/Circ.1370 Annex,page2
Measurement	Flammable gas (%LEL / %VOL)
User interface	Touch screen (10") for choosing the sample point, alarm stop & reset, skip, etc.
Alarm settings	Fully adjustable between zero and full scale
Audible alarm	-95dB @ 30cm
Relay output	Gas alarm Sensor trouble, Flow fail, Communication fail, Controller trouble, Panel inside and other system abnormal alarms
Communication configuration	RS-485/RS-422 & MODBUS communication

Painting	Powder coating with customer's requirement
Ingress Protection	IP65
Fixing details	Self standing type / Wall mounting type
Filter equipment	On line filter
Power supply	AC220V, 60Hz / DC24V(optional)
Power consumption	Max. 500VA (Alarm condition)
Other function	Auto drain, Manual purge, etc Repeater alarm unit with display
Approval	MED, ABS, DNV, KR, RINA type approved LR, BV, NK, CCS are available
Sales refer.	More than 70 vessels

Distributed by



Uniservice Unisafe S.r.l.

T (+39) 010.714.647 F (+39) 010.717.0293
www.uniservicesafety.com info@uniservicesafety.com